



Spreaders **APOLLO** are meet needs of medium and large farms. Machines are equipped with wheel set based on single axle, large wheels guarantee lesser rolling resistance and allow easier moving on difficult wet ground. Two-shaft adapter used in the spreaders constitutes universality and effectiveness for manure, lime or light poultry manure spreading.

Standard equipment:

- vertical 2-shaft adapter or horizontal and disc adapters
- stepless hydraulic control of floor conveyor
- handbrake
- pneumatic single- or double-line brake / hydraulic brake
- power transmitter shaft
- mechanic support
- complete lightning installation
- low hitch
- container shutter
- operational width – vertical 2-shaft adapter: 6÷8 m
- operational width – 2-shaft horizontal and disc adapters: 12÷24 m

Technical specification:

TYPE		APOLLO 8	APOLLO 11	APOLLO 14	APOLLO 14
Adapter		vertical 2-shaft	vertical 2-shaft	vertical 2-shaft	horizontal 2-shaft + disc
Tank capacity [m ³]		10	12,5	14	14
Load [t]		6,5	7	10	10
Working width [m]		8÷12	8÷12	8÷12	12÷24
Total length [m]		7,1	7,6	8,25	8,25
Total width [m]		2,55	2,8	2,95	2,95
Total height [m]		2,75	2,8	3,09	3,09
Tyres		18,4×38	23,1×38	650/75×R32 und 580/70 R38	
Load box sizes [m]	Width	1,50/1,90	1,50/1,90	1,50/1,90	
	Length	4,08	4,48	5,48	
	Height	1,29	1,29	1,4	
Mass [kg]		4 840	4 840	5 640	5 720
Power demand [HP]		80	90	100	100
Price [EUR]		18 800	22 000	25 100	26 900

Additional equipment:

Electric controlling of floor conveyor

1 150 EUR



VERTICAL TWO-SHAFT ADAPTER

Spreaders TYTAN 14, 18, 22 may be equipped with an universal two-shaft worm adapter of wide spreading range in standard. Two massive shafts quickly process manure or other materials fed by the floor scoops. Big spreading discs with four blades, which are precisely shaped and resistant to attrition, allow to attain spreading width up to over a dozen meters with good evenness of spreading at the same time. With the help of two-shaft adapter you may spread manure, peat as well as lime. The exchangeable cutting and tearing screw knives are made of high quality steel and serve for long-term and trouble-free work.



HORIZONTAL ADAPTER + SHIELD ADAPTER

Adapter APOLLO 14 may be equipped with shield adapter with horizontal two-shaft worm adapter (with exchangeable cutting knives). Such solution is perfect for spreading slime, compost and peat for distance from 12 to 24 m.