



Mounted disc harrow is used for loosening and crushing soil. They are suitable for working on stubble as well as mixing fertilizer and plant remains with soil. They have modular construction allowing connecting levelling roller and installing seeder for aftercrop.

### Standard equipment:

#### CUT L

- four sections of discs placed in „X” arrangement
- toothed discs  $\varnothing 510$  mm or  $\varnothing 560$  mm
- frame 100×100×6 mm

#### CUT XL

- four sections of discs placed in “X” arrangement
- toothed discs  $\varnothing 610$  mm or  $\varnothing 660$  mm
- frame 120×120×8 m

### Technical specification:

TYPE	CUT L 2,3×510	CUT L 2,3×560	CUT L 2,8×510	CUT L 2,8×560	CUT L 3,2×510	CUT L 3,2×560	CUT L 3,9×560
Mass [kg]	750	780	790	820	880	920	1000
Power demand [HP]	60÷80	60÷80	70÷95	75÷100	85÷110	85÷110	110÷140
Number of discs [pcs]	20	20	24	24	28	28	36
Price [EUR]	2 450	2 750	3 000	3 550	3 550	4 000	4 850
Surcharge for Pipe roller $\varnothing 600$ [EUR]	950	950	1 100	1 100	1 250	1 250	1 400

TYPE	CUT XL 2,8×610	CUT XL 2,8×660	CUT XL 3,2×610	CUT XL 3,2×660	CUT XL 3,9×610	CUT XL 3,9×660
Mass [kg]	1270	1360	1380	1500	1500	1620
Power demand [HP]	80÷105	85÷110	95÷120	100÷125	125÷160	130÷165
Number of discs [pcs]	24	24	28	28	36	36
Price [EUR]	6 050	6 710	6 820	7 920	7 480	8 470
Surcharge for Pipe roller $\varnothing 600$ [EUR]	1 300	1 300	1 550	1 550	1 850	1 850

### Additional equipment:

Middle tine	210 EUR
Carriage for semi-mounted version	2 350 EUR
Coupler for seeder at the carriage	280 EUR



The biggest of Cut XXL disc harrows. Available only in semi-mounted version. It is hydraulically foldable for transport. It has option of increasing weight of the harrow by filling the frame with water.

### Standard equipment:

- four sections of discs placed in “X” arrangement
- toothed discs  $\varnothing 660$  mm
- pipe roller  $\varnothing 600$  mm
- main frame 180×260 mm



### Technical specification:

TYPE	CUT XXL 5,0×660	CUT XXL 6,0×660	CUT XXL 7,0×660
Mass/Mass with water [kg]	5 650/6 150	5 900/6 400	6 150/6 650
Power demand [HP]	170÷210	180÷240	200÷270
Number of discs [pcs]	44	52	60
Price with Pipe roller [EUR]	23 700	25 800	28 400

### Additional equipment:

Hydraulic adjustment of working depth (surcharge for one point of adjustment)

260 EUR