



Machines designed for loosening soil without overturning it at depth up to 35 cm. It causes better percolation as well as drainage of soil's top layer. In addition, Kret Plows can form a system together with cultivators Ares T or seeding machines.



Standard equipment:

- bolt protection of tines (version B) or non-stop spring leaves protection (version S)
- underbeam clearance 950 mm
- 2 pcs. of rubber support wheels
- working depth up to 35 cm
- exchangeable coulter
- adjustable distance between tines

Technical specification:

TYPE	4 B	6 B	8 B	4 S	6 S	8 S
Mass [kg]	840	1140	1400	1210	1600	2030
Power demand [HP]	130÷150	150÷180	170÷200	130÷150	150÷180	170÷200
Working width [m]	3	3	4	3	3	4
Price [EUR]	3 100	4 200	5 400	4 500	6 500	8 550
Price with fixing plates to roller [EUR]	3 645	4 745	5 945	5 045	7 045	9 095
Surcharge for Pipe roller ø600 mm [EUR]	1 940	1 940	2 510	2 090	2 090	2 660
Surcharge for Packer roller ø500 mm [EUR]	1 940	1 940	2 510	2 090	2 090	2 660
Surcharge for Rubber roller ø500 mm [EUR]	3 150	3 150	4 085	3 300	3 300	4 235
Surcharge for Spiral roller XL [EUR]	3 750	3 750	4 910	3 900	3 900	5 060
Surcharge for Croskill roller ø400 mm [EUR]	3 090	3 090	4 030	3 240	3 240	4 180

Additional equipment:

Plow system to attach to other machines (4B; 6B; 8B)	600 EUR
Plow system to attach to other machines (4S; 6S; 8S)	1 050 EUR
Carriage for semi-mounted version (4B; 6B; 8B)	3 150 EUR
Carriage for semi-mounted version (4S; 6S; 8S)	3 400 EUR



Subsoilers are designed for crushing and loosening of deep-seated layers of soil, which were not moved during traditional ploughing. They can work at depth up to 50 cm, improving soil conditions through better percolation and its oxygenation.



Standard equipment:

- bolt protection of tines (version B) or non-stop spring protection (version S)
- underbeam clearance 900mm
- 2 tin support wheels $\varnothing 550 \times 160$ (models 3B i 5B) or 2 rubber support wheels $\varnothing 600 \times 200$ (version 3S, 5S, 7S, 7B)
- working depth up to 50 cm
- exchangeable coulters with wings
- wide frame 100x200 mm
- undrcutting width 150 mm
- adjustable distance between tines

Technical specification:

TYPE	KRET 3 B	KRET 5 B	KRET 7 B	KRET 3 S	KRET 5 S	KRET 7 S
Mass [kg]	610	840	1140	830	1300	1785
Power demand [HP]	75÷110	110÷150	160÷210	100÷130	150÷180	180÷240
Working width [m]	1,68	2,80	3,92	1,68	2,80	3,92
Price [EUR]	2 550	3 350	4 800	4 250	6 200	8 100
Surcharge for Pipe roller $\varnothing 600$ [EUR]	—	1 150	1 500	—	1 150	1 500
Surcharge for Rubber roller $\varnothing 500$ [EUR]	—	2 100	2 800	—	2 100	2 800

Additional equipment:

Surcharge – rubber wheel (3B; 5B)

200 EUR