



Economic rotary mowers, mounted at the back of the tractor, should be used to mow all kinds of low-stalk plants for hay and further processing. They are characterized by high efficiency and reliability. They have firm, solid construction and are produced in high quality. Available working widths [m]: 1,35; 1,65; 1,85; 2,10.



### Standard equipment:

- Upper metal cover
- Low cover – plavil
- Spring safety device
- Swath opener for Mewa 1,85K and Mewa 2,10K

### Technical specification:

TYPE	MEWA 1,35	MEWA 1,65	MEWA 1,85	MEWA 2,10	MEWA 1,85 K	MEWA 2,10 K
Mower type	mounted					
Mass [kg]	330	360	410	520	480	620
Working width [m]	1,35	1,65	1,85	2,10	1,85	2,10
Number of knives [pcs]	4	6	6	8	6	8
Mowing height [cm]	4,2	4,2	4,2	4,2	4,2	4,2
Efficiency [ha/h]	1,4	1,7	2,0	2,4	2,0	2,4
Max. Working speed [km/h]	15	15	15	15	15	15
Power demand [HP]	25	40	40	80	60	80
Price [EUR]	1 550	1 730	2 390	2 990	3 700	4 350

### Additional equipment:

Hydraulic suspension system for MEW A 1,65	300 EUR
Hydraulic suspension system for MEW A 1,85	375 EUR
Hydraulic suspension system for MEW A 2,10	375 EUR
PTO shaft for 1,35; 1,65; 1,85	175 EUR