

RAK 1

Single wheel rakes



RAK 1 is easy to operate and efficient machine for raking grass, hay and straw. Because of small power demand, machine is extremely economic and resistant to difficult working conditions. Rake forms even and continual row of swath placed on the left side of tractor's passage.

Standard equipment:

- One working wheel (3,8)
- Automatic transmission
- Spoke arms foldable for transport
- Adjustment of working height
- Pneumatic copying wheels



Technical specification:

TYPE	RAK 1
Working width [m]	3,8
Width of formed row [m]	0,7
Transport Width [m]	1,5
Transport Height [m]	3,4
Number of arms [pcs]	9
Efficiency [ha/h]	3,6
Power demand [HP]	45
Mass [kg]	340
Number of rotors [pcs]	1
Diameter of rotors [m]	3,3
Price [EUR]	2 270

RAK 2

Double wheel rakes



RAK 2 is a double wheel rake designed for forming even swaths of hay, straw and green fodder. Rake's working width is adjustable in range from 6,4 to 7,4. Densely spaced arms provide unique effectiveness and speed. Rake forms even, regular swath placed centrally between rotors. Material's fibers are placed lengthwise, what makes smooth work of collecting machinery easier.

Standard equipment:

- Two working rotors
- Hydraulically adjusted working width
- Hydraulically foldable for transport
- Wide wheels
- Solid construction of frame
- Adjustable working height
- Pneumatic copying wheels for each rotor



Technical specification:

TYPE	RAK 2
Working width [m]	6,4÷7,4
Width of formed row [m]	0,7÷1,7
Transport Width [m]	2,6
Transport Height [m]	3,4
Number of arms [pcs]	2×11
Efficiency [ha/h]	8,5
Power demand [HP]	70
Mass [kg]	1870
Number of rotors [pcs]	2
Diameter of rotors [m]	3,2
Price [EUR]	13 500