

Trailed fertilizer and lime spreader



RCW spreaders are an offer for users farming in difficult soil conditions. Offered capacities from 3000 to 10000 litres allow matching spreader's size to farm's needs. They are equipped with two spreading systems in standard ie for lime and for fertilizer – it allows selecting optimal parameters of spreader's work in accordance to spreaded materials.

Standard equipment:

- one-axle spreader (RCW 3000, RCW 5500)
- spring tandem spreader (RCW 10000)
- belt conveyor
- towing bar's support
- lightning installation
- handbrake
- single-line or double-line pneumatic brake
- border disc
- stepless regulated damper
- conveyor's drive from spur wheel
- shields' drive hydraulic or mechanic
- discs for fertilizer and lime made of stainless steel
- low or upper hitch
- wheels RCW 3000 – 12,5/80×18
- wheels RCW 5500 – 500/60×22,5
- wheels RCW 7500 – 550/60×22,5
- wheels RCW 10 000 – 500/60×22,5

Technical specification:

TYPE	RCW 3000	RCW 5500	RCW 7500	RCW 10000
Tank capacity [dm ³]	3 000	5 500	7 500	10 000
Working width [m]	lime	8÷16	8÷16	8÷16
	granular fertilizer	10÷36	10÷36	10÷36
Sizes [mm]	length	4 950	5 700	6 800
	width	2 100	2 200	2 200
	height	1 950	2 230	2 430
Mass [kg]	1 840	2 115	2 250	2 600
Power demand [HP]	60	80	100	120
Discs drive	hydraulic/mechanic			
Conveyor drive	for spur wheel			
Price [EUR]	11 450	14 450	15 910	19 060

Additional equipment:

Cover (RCW 3000)	265 EUR
Cover (RCW 5500, 7500)	395 EUR
Cover (RCW 10000)	510 EUR
Capacity extension to 4000 l (RCW 3000)	420 EUR

Trailed fertilizer and lime spreader



Spreaders **RCW plus** are equipped with large wheels which are perfect for spreading lime and fertilizing crops in row tillage. Adjustable distance between wheels in range from 1800 to 2000 in RCW 5500 plus spreaders allows adjusting distance between wheels in accordance to owned tractor.

Standard equipment:

- one-axle spreader (RCW 5500 plus, RCW 7500 plus)
- belt conveyor
- towing bar's support
- lightning installation
- handbrake
- single-line or double-line pneumatic brake
- border disc
- stepless regulated damper
- conveyor's drive hydraulic
- shields' drive mechanic
- discs for fertilizer and lime made of stainless steel
- low or upper hitch
- wheels RCW 5500 plus – 340/85 R48
- wheels RCW 5500 plus – 20,8 R 42

Technical specification:

TYPE		RCW 5500 PLUS	RCW 7500 PLUS
Tank capacity [dm ³]		5 500	7 500
Working width [m]	lime	8÷16	8÷16
	granular fertilizer	10÷36	10÷36
Sizes [mm]	length	5,7	5,7
	width	2,29	2,55
	height	2,45	2,72
Mass [kg]		2 200	2 450
Power demand [HP]		80	100
Discs drive		mechanic	
Conveyor drive		hydraulic	
Price [EUR]		16 070	17 250



Kalkadapter



Düngeradapter

Additional equipment:

Cover

455 EUR