



Classical, light mounted ploughs for medium and deep bed-ploughing. Wide range of bed-ploughs suitable for different client's needs.

Standard equipment:

- changeable ploughing width – 30 or 35 cm (version B 30/35-3) and fixed 35 or 40 (version B) per body
- bolt protection of bodies (B), non stop five-blades spring leaves protection
- adjustment of the first furrow by bolts
- tin support wheel (version B 30/35-3)
- rubber support wheel (version B)
- disc coulter \varnothing 405 mm (version B 30/35-3)
- disc coulter \varnothing 480 mm (version B)
- plough furrow MX (version B 30/35-3; B 35; R 35)
- plough furrow ZX (version B 40; R 40)

Technical specification:

TYPE	TUR B 30/35-3	TUR B 35 3+	TUR B 35 3+1	TUR B 35 4+	TUR B 35 4+1	TUR B 40 3+	TUR B 40 3+1	TUR B 40 4+	TUR B 40 4+1
Mass [kg]	370	560	660	660	750	560	670	670	770
Power demand [HP]	45÷60	45÷60	60÷80	60÷80	80÷110	60÷80	80÷110	80÷110	110÷150
Interbody clearance [cm]	76/88	85	85	85	85	90	90	90	90
Underbeam clearance [cm]	66	75	75	75	75	75	75	75	75
Price [EUR]	1 550	2 700	3 200	3 300	3 700	3 150	3 600	4 000	4 450
Price of CORN version [EUR]	1 700	—	—	—	—	3 550	4 200	4 600	5 150

TYPE	TUR R 35 3+	TUR R 35 3+1	TUR R 35 4+	TUR R 35 4+1	TUR R 40 3+	TUR R 40 3+1	TUR R 40 4+	TUR R 40 4+1
Mass [kg]	760	910	950	990	760	930	980	1150
Power demand [HP]	45÷60	60÷80	60÷80	80÷110	60÷80	80÷110	80÷110	110÷150
Interbody clearance [cm]	85	85	85	85	90	90	90	90
Underbeam clearance [cm]	75	75	75	75	75	75	75	75
Price [EUR]	4 150	5 050	5 150	6 150	4 550	5 500	6 200	6 850

Additional equipment:

Openwork body (Surcharge to MX) TUR B 30/35-3, B 35 Set	250 EUR
Openwork body (Surcharge to ZX) TUR B 40	275 EUR
Beam for attachment tool	130 EUR
Enhancement of the Tur R (2 blades and disc), Set	100 EUR



Bed-ploughs Tur Vario with side cylinder for fluent adjustment of ploughing width from 35 to 50 per furrow. A quick correction of the working width depending on type of soil can be made.

Standard equipment:

- fluently adjusted working width in range 35÷50 cm
- bolt protection of bodies (B)
- non-stop seven-blades spring leaves protection of bodies (R)
- frame 120×120 mm
- rubber support wheel
- plough furrow ZX
- disc coulter ø480 mm
- side cylinder (Tur Vario 4 and 5)



Technical specification:

TYPE	VARIO 4B	VARIO 5B	VARIO 6B	VARIO 7B	VARIO 4R	VARIO 5R
Mass [kg]	860	1060	1100	1230	1040	1240
Power demand [HP]	90÷120	110÷150	160÷190	220÷250	90÷120	110÷150
Interbody clearance [cm]	100	100	100	85	85	85
Underbeam clearance [cm]	80	80	80	75	75	75
Price [EUR]	4350	5550	6400	7500	5700	7350

Additional equipment:

Openwork body (Surcharge to ZX), Set	275 EUR
Vorschäler	135 EUR
Beam for attachment tool	130 EUR
Enhancement of the Tur R (2 blades and disc), Set	100 EUR